

VARIABLE OUTPUT LED 30K GRILL TOP WELL LIGHT

15705BZ-LMA30K

VARIABLE OUTPUT LED 3K GRILL TOP WELL
LIGHT



| DETAILS | |
|-----------|------------|
| FINISH: | Bronze |
| MATERIAL: | Aluminum |
| GLASS: | Clear Lens |
| DIMMABLE: | No |

| DIMENSIONS | |
|------------|------|
| WIDTH: | 4.8" |
| HEIGHT: | 4.8" |
| DEPTH: | 4.8 |
| WEIGHT: | 3lb |

| LIGHT SOURCE | |
|---------------------------|--|
| LIGHT SOURCE: | Integrated LED |
| LED NAME: | 30G4SE-12W |
| WATTAGE: | 12w, 8w, 5w, 3w LumaCore LED *Included |
| VOLTAGE: | 12v |
| COLOR TEMP: | 3000 |
| CRI: | 80 |
| INCANDESCENT EQUIVALENCY: | 1 x 60w, 45w, 35w, 25w |
| DIMMABLE: | No |
| TRANSFORMER REQUIRED: | Yes |

| MOUNTING | |
|------------|---------|
| LEAD WIRE: | 1 X 36" |

| SHIPPING | |
|----------------|------|
| CARTON LENGTH: | 7 |
| CARTON WIDTH: | 7 |
| CARTON HEIGHT: | 13.5 |
| CARTON WEIGHT: | 4.5 |

PRODUCT DETAILS:

- Wattage settings includes: 3W (260 Lumens), 5W (350 Lumens), 8W (475 Lumens), 12W (750 Lumens)
- Suitable for use in wet (outdoor direct rain or sprinkler) locations as defined by NEC and CEC. Meets United States UL Underwriters Laboratories & CSA Canadian Standards Association Product Safety Standards
- Photometrics based off engine photometrics.
- Incorporates CREE LEDs with application performance tested by CREE
- PVC constructed concrete pour kit and burial sleeve is supplied.
- Includes a dense foam cap to prevent concrete from entering
- LumaCore Series products carry a lifetime limited warranty
- Sophisticated and streamlined design, durable construction and timeless finish complement any architectural style

HINKLEY

HINKLEY
33000 Pin Oak Parkway
Avon Lake, OH 44012

PHONE: (440) 653-5500
Toll Free: 1 (800) 446-5539

hinkley.com